

### **REMARKS/ARGUMENTS**

It was noted that a certified copy of the application filed in Germany to which foreign priority is claimed has not yet been filed. Claims 15 to 24 were rejected under 35 U.S.C. § 103(a) as being unpatentable over either U.S. Patent No. 3,552,886 to Olson or U.S. Pub. No. 2002/0039531 to Morita et al. in view of U.S. Pub. No. 2002/0129603 to Schorr et al. Claims 25 to 31 were objected to as being dependent upon a rejected base claim.

A certified copy of the application filed in Germany to which foreign priority is claimed has been submitted herewith. An updated Application Data Sheet that reflects the current application information has been submitted herewith.

Reconsideration of the application is respectfully requested.

#### **Priority Document**

It was noted that a certified copy of German Patent Application No. 102 30 058.5, filed July 4, 2002, to which foreign priority is claimed through International Patent Application Serial No. PCT/DE2003/002218, filed July 3, 2003, has not yet been filed. Although the International Bureau should have provided a certified copy of the priority document, a certified copy of German Patent Application No. 102 30 058.5 is submitted herewith.

#### **Specification**

Instructions from the preliminary amendment filed January 4, 2005 regarding the Abstract were erroneously added to the specification as paragraph [0001] as shown in the published application US 2006/0207423 A1 (i.e. "Please replace the Abstract as presented . . .").

It is thus respectfully requested that erroneous [0001] be removed and the paragraphs within the specification be renumbered accordingly.

#### **35 U.S.C. 103 Rejections**

Claims 15 to 24 were rejected under 35 U.S.C. § 103(a) as being unpatentable over either U.S. Patent No. 3,552,886 to Olson or U.S. Pub. No. 2002/0039531 to Morita et al. in view of U.S. Pub. No. 2002/0129603 to Schorr et al.

Olson shows a compressor unit with self-contained drive means. Figure 1 of Olson shows “a housing 10 with a main smooth bore bounded by a series of internal threads 11 around an annular surface at one end and by an inturned flange 12 at the opposite end” (col. 3, lines 15 to 18 of Olson). “The internal threads 11 mate with the external threads 13 formed in an annular retaining ring 14, which, when threaded into the housing end, may compress an O-ring 15 tightly against the outturned annular shoulder 16 of an end bell 17” (col. 3, lines 18 to 23 of Olson).

Morita et al. shows a “refrigerant compressor [that] includes a cylinder block, a front housing, and a sealing member” (Abstract of Morita et al.). “In compressor 100, front housing 6 and cylinder block 1 are joined by engaging external thread 6a of front housing 6 with internal thread 1b of cylinder block 1” (Specification at [0021] of Morita et al.). “The joint portion between external thread 6a and internal thread 1b is sealed by O-ring 10” (id.). “The strength of the joint portion between front housing 6 and cylinder block 1 may be increased by adjusting a height of the thread, a pitch of the thread, the number of threads of external thread 6a and internal thread 1b, or combination thereof” (id.).

Schorr et al. shows a device to reduce vibrations in a hydraulic force transfer system. “[A] design is preferred according to which the cover is attached to the housing by means of a threaded connection” (Specification at [0016] of Schorr et al.). “Such a threaded connection firstly allows easy replacement of the membrane” (id.). “The threaded connection is preferably structured as both a sawtooth and a round thread” (Specification at [0017] of Schorr et al.). In addition the threaded connection described above has advantages in that due to the sawtooth thread-like structure on the internal diameter of the thread profile on the housing a greater thread bearing depth can be achieved than with a conventional trapezoid thread, whereas the round thread-like structure on the external diameter of the thread profile on the housing ensures a reduction in notch effect in comparison with conventional trapezoid thread, which is particularly important for the durability of the housing when plastic is used as a housing material” (id.).

Claim 15 recites: A reciprocating piston-type machine, comprising:  
a housing;  
a housing cover;  
a power unit disposed in the housing and including a plurality of pistons;  
one of a suction and discharge area and a forward shaft bearing disposed in the housing cover; and  
a screw connection configured to screw-couple the housing cover to the housing, the screw connection including saw tooth thread between the housing and the housing cover.

As admitted in the Office Action, neither Olson nor Morita et al. shows a saw tooth thread. It is respectfully submitted that it would not have been obvious to one having ordinary skill in the art to combine Olson or Morita et al. with Schorr et al. as asserted in the Office Action.

Schorr et al. shows a hydraulic force transfer system which is not similar to the compressors of Olson and Morita. Such compressors have been known for a long time, as have saw tooth threads. However, as discussed in the present application, compressor teeth have been v-shaped. As taught by Morita, those of skill in the art have changed the strength of compressor housing joints by “increasing a height of the thread, a pitch of the thread, the number of threads of the external thread and the internal thread, and combinations thereof.” Morita and the prior art thus teach away from using saw tooth threads.

Schorr also teaches that the bearing depth is important for plastic housings, which Olson and Morita do not have.

The proposed motivation is also not understood, as there is no reason or need for Olson or Morita to have a greater thread bearing depth as asserted.

Withdrawal of the rejection to claim 15 and its dependent claims under 35 U.S.C. §103(a) is thus respectfully requested.

Claim Objections

Claims 25 to 31 were objected to as being dependent upon a rejected base claim but were indicated as being allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.


In light of the above with respect to claim 15, withdrawal of the objection to claims 25 to 31, which depend from claim 15, is respectfully requested.

**CONCLUSION**

The present application is respectfully submitted as being in condition for allowance and applicants respectfully request such action.

Respectfully submitted,

DAVIDSON, DAVIDSON & KAPPEL, LLC

By   
William C. Gehris, Reg. No. 38,156

DAVIDSON, DAVIDSON & KAPPEL, LLC  
485 Seventh Avenue, 14<sup>th</sup> Floor  
New York, New York 10018  
Tel: (212) 736-1940  
Fax: (212) 736-2427